



# SAFETY DATA SHEET

Version #: 01  
Issue date: 06-September-2023  
Revision date: -  
Supersedes date: -

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** STEEL-IT 1002B Polyurethane Aerosol – Steel Gray

**Registration number** -

**Synonyms** None.

**SDS number** SDS-1002B

**Product code** FGAE1002B (14 oz.), FGAE1002C (4.5 oz. ), CASE1002B (case of 12 FGAE1002B), CASE1002C (case of 12 FGAE1002C)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint / Industrial coating (topcoat).  
Category: Pigmented metallic coating.

**Uses advised against** Uses other than the recommended use.  
Do not spray on an open flame or other ignition source.

### 1.3. Details of the supplier of the safety data sheet

**Manufacturer** Stainless Steel Coatings, Inc.  
**Address** 835 Sterling Road, Lancaster MA 01523-2915, USA  
**Telephone** +1 (978) 365-9828  
**E-mail** sds@STEEL-IT.com

**Supplier** HM Industrieservice GmbH  
**Address** Großer Sand 3  
76698 Ubstadt-Weiher, Germany  
**Telephone** +49 7251 44127-0  
**Fax** +49 7251 44127-29  
**E-mail** info@hm-industrie.de  
**Website** www.hm-industrie.de

**1.4. Emergency telephone number** CHEMTREC:  
+1-703-527-3887 (International)

**General in EU** 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Austria National Poisons Information Centre** +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Belgium National Poisons Control Centre** 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Bulgaria National Toxicological Information Centre** +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Croatia Poisons Information Centre** +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

**Cyprus Poison Centre** 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Czech Republic National Poisons Information Centre** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

<b>Denmark National Poisons Control Centre</b>	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Estonia National Poisons Information Centre</b>	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
<b>Finland National Poison Information Centre</b>	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>France National Poisons Control Centre</b>	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Greece Poison Information Centre telephone number</b>	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Hungary National Emergency Phone Number</b>	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Iceland Poison Centre</b>	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Latvia Emergency medical aid</b>	113
<b>Latvia Poison and Drug Information Centre</b>	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Lithuania Neatidėliotina informacija apsinuodijus</b>	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Malta Accident and Emergency Department</b>	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Netherlands National Poisons Information Centre (NVIC)</b>	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Centre</b>	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Portugal Poison Centre</b>	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Romania Biroul RSI si Informare Toxicologica</b>	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
<b>Slovakia National Toxicological Information Centre</b>	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Spain Toxicology Information Service</b>	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Sweden National Poison Information Centre</b>	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Switzerland Tox Info Suisse</b>	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Ireland National Poisons Information Centre</b>	353 (1) 809 2566 Healthcare Professionals: 24 hours, 7 days a week

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

##### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.

Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 1B	H350 - May cause cancer.
Reproductive toxicity (inhalation)	Category 2	H361 - Suspected of damaging fertility or the unborn child by inhalation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (inhalation)	Category 2 (respiratory tract)	H373 - May cause damage to organs (respiratory tract) through prolonged or repeated exposure by inhalation.
<b>Environmental hazards</b>		
Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** Acetone, Benzene, 1-chloro-4-(trifluoromethyl)-, Butanone oxime, Distillates (petroleum), hydrotreated light, Nickel, Xylene

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child by inhalation.
H373	May cause damage to organs (respiratory tract) through prolonged or repeated exposure by inhalation.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

##### Response

P308 + P311	IF exposed or concerned: Call a POISON CENTRE/doctor.
-------------	---

##### Storage

Not assigned.

##### Disposal

Not assigned.

#### Supplemental information on the label

Restricted to professional users.  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.  
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

## 2.3. Other hazards

May displace oxygen and cause rapid suffocation.  
This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.  
The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.  
The mixture does not contain any substances having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1% by weight.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

## General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Benzene, 1-chloro-4-(trifluoromethyl)-	15 - 25	98-56-6 202-681-1	-	-	
<b>Classification:</b> Flam. Liq. 3;H226, Skin Sens. 1B;H317, Carc. 2;H351, Repr. 2;H361, Aquatic Chronic 2;H411					
Propane	10 - 20	74-98-6 200-827-9	-	601-003-00-5	
<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280					
Acetone	5 - 15	67-64-1 200-662-2	-	606-001-00-8	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 <b>Supplemental Hazard Statement(s):</b> EUH066					
Distillates (petroleum), hydrotreated light	5 - 15	64742-47-8 265-149-8	-	649-422-00-2	
<b>Classification:</b> Flam. Liq. 3;H226, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Butane	5 - 10	106-97-8 203-448-7	-	601-004-01-8	
<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280					
Chromium	< 2	7440-47-3 231-157-5	-	-	#
<b>Classification:</b> -					
C.I. Pigment black 028	< 2	68186-91-4 269-053-7	-	-	#
<b>Classification:</b> -					
Xylene	< 2	1330-20-7 215-535-7	-	601-022-00-9	#
<b>Classification:</b> Flam. Liq. 3;H226, Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 4;H332;(ATE: 11 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, STOT SE 3;H335;H336, STOT RE 2;H373, Asp. Tox. 1;H304					
Nickel	< 2	7440-02-0 231-111-4	-	028-002-01-4	
<b>Classification:</b> Skin Sens. 1;H317, Carc. 2;H351, STOT RE 1;H372					
C.I. Pigment Blue 28	< 0,3	1345-16-0 310-193-6	-	-	
<b>Classification:</b> -					
Butanone oxime	< 0,2	96-29-7 202-496-6	-	616-014-00-0	
<b>Classification:</b> Acute Tox. 3;H301;(ATE: 100 mg/kg bw), Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Skin Irrit. 2;H315, Eye Dam. 1;H318, Skin Sens. 1;H317, Carc. 1B;H350, STOT SE 1;H370, STOT SE 3;H336, STOT RE 2;H373					

## List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

## Composition comments

The full text for all H-statements is displayed in section 16.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. Components not listed are either non-hazardous or are below reportable limits.

## SECTION 4: First aid measures

### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Do not induce vomiting without advice from poison control centre. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Narcosis. Headache. Fatigue. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable aerosol. Contents under pressure. Pressurised container may explode when exposed to heat or flame.

#### 5.1. Extinguishing media

**Suitable extinguishing media** Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed such as: Carbon oxides. Chlorine compounds. Fluorine compounds. Fumes of metal oxides.

#### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Special fire fighting procedures** In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. Fight fire from protected location or safe distance. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours/spray. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**For emergency responders** In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours/spray. Emergency personnel need self-contained breathing equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

#### 6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains.

Pick up undamaged aerosol cans mechanically. Dike leaked material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water. Retain and dispose of contaminated wash water.

Never return spills to original containers for re-use. Put material in suitable, covered, labelled containers.

### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded.

Do not breathe mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Persons susceptible for allergic reactions should not handle this product. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Mechanical ventilation or local exhaust ventilation may be required. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO<sub>2</sub> = 135 mmHg). Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat, sparks and open flame. Store in original tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see section 10 of the SDS).

TRGS 510 storage class: 2B.

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P3a FLAMMABLE AEROSOLS (Lower-tier requirements = 150 (net) tonnes; Upper-tier requirements = 500 (net) tonnes)

- P3a FLAMMABLE AEROSOLS (Lower-tier requirements = 150 (net) tonnes; Upper-tier requirements = 500 (net) tonnes)

- P3b FLAMMABLE AEROSOLS (Lower-tier requirements = 5 000 (net) tonnes; Upper-tier requirements = 50 000 (net) tonnes)

- P3b FLAMMABLE AEROSOLS (Lower-tier requirements = 5 000 (net) tonnes; Upper-tier requirements = 50 000 (net) tonnes)

- P3b FLAMMABLE AEROSOLS (Lower-tier requirements = 5 000 (net) tonnes; Upper-tier requirements = 50 000 (net) tonnes)

- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tonnes; Upper-tier requirements = 500 tonnes)

### 7.3. Specific end use(s)

Paint / Industrial coating (topcoat).

Category: Pigmented metallic coating.

Observe industrial sector guidance on best practices.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List Components

Components	Type	Value
Acetone (CAS 67-64-1)	MAK	1200 mg/m <sup>3</sup>
		500 ppm
	STEL	4800 mg/m <sup>3</sup>
		2000 ppm

**Austria. MAK List  
Components**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Butane (CAS 106-97-8)	Ceiling	3800 mg/m3 1600 ppm
	MAK	1900 mg/m3 800 ppm
	MAK	2 mg/m3
Chromium (CAS 7440-47-3)	MAK	2 mg/m3
Propane (CAS 74-98-6)	Ceiling	3600 mg/m3 2000 ppm
	MAK	1800 mg/m3 1000 ppm
	MAK	221 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	MAK	221 mg/m3 50 ppm
	STEL	442 mg/m3 100 ppm

**Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -  
Chemical agents, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	1187 mg/m3 492 ppm
	TWA	594 mg/m3 246 ppm
	STEL	2370 mg/m3 980 ppm
Butane (CAS 106-97-8)	STEL	2370 mg/m3 980 ppm
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3
Nickel (CAS 7440-02-0)	TWA	1 mg/m3
Propane (CAS 74-98-6)	TWA	1000 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

**Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as  
amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	1400 mg/m3
	TWA	600 mg/m3
Butane (CAS 106-97-8)	TWA	1900 mg/m3
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m3
Chromium (CAS 7440-47-3)	TWA	2 mg/m3
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3
Xylene (CAS 1330-20-7)	STEL	442 mg/m3 100 ppm
	TWA	221 mg/m3 50 ppm

**Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and  
Biological Limit Values, Annex I (NN 91/2018), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Acetone (CAS 67-64-1)	MAC	1210 mg/m3 500 ppm	

**Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended**

Components	Type	Value	Form
Butane (CAS 106-97-8)	MAC	22 mg/m <sup>3</sup>	
		10 ppm	
	STEL	1810 mg/m <sup>3</sup>	
C.I. Pigment black 028 (CAS 68186-91-4)	MAC	0,2 mg/m <sup>3</sup>	Total dust.
		0,05 mg/m <sup>3</sup>	Respirable dust.
Chromium (CAS 7440-47-3)	MAC	2 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	MAC	0,5 mg/m <sup>3</sup>	
Xylene (CAS 1330-20-7)	MAC	221 mg/m <sup>3</sup>	
		50 ppm	
	STEL	442 mg/m <sup>3</sup>	
		100 ppm	

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended**

Components	Type	Value
Nickel (CAS 7440-02-0)	TWA	1 mg/m <sup>3</sup>

**Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	Ceiling	1500 mg/m <sup>3</sup>	
	TWA	800 mg/m <sup>3</sup>	
C.I. Pigment black 028 (CAS 68186-91-4)	Ceiling	1,5 mg/m <sup>3</sup>	Aerosol, inhalable.
	TWA	0,5 mg/m <sup>3</sup>	Aerosol, inhalable.
Chromium (CAS 7440-47-3)	Ceiling	1,5 mg/m <sup>3</sup>	Aerosol, inhalable.
	TWA	0,5 mg/m <sup>3</sup>	Dust.
		0,5 mg/m <sup>3</sup>	Aerosol, inhalable.
Iron (Massive metal) (CAS 7439-89-6)	TWA	10 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	Ceiling	1 mg/m <sup>3</sup>	Aerosol, inhalable.
	TWA	0,5 mg/m <sup>3</sup>	Aerosol, inhalable.
Xylene (CAS 1330-20-7)	Ceiling	400 mg/m <sup>3</sup>	
	TWA	200 mg/m <sup>3</sup>	

**Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TLV	600 mg/m <sup>3</sup>	
		250 ppm	
Butane (CAS 106-97-8)	TLV	1200 mg/m <sup>3</sup>	
		500 ppm	

**Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2**

Components	Type	Value	Form
C.I. Pigment black 028 (CAS 68186-91-4)	TLV	0,5 mg/m <sup>3</sup>	
Chromium (CAS 7440-47-3)	TLV	0,5 mg/m <sup>3</sup>	Dust.
Nickel (CAS 7440-02-0)	TLV	0,05 mg/m <sup>3</sup>	Dust.
Propane (CAS 74-98-6)	TLV	1800 mg/m <sup>3</sup> 1000 ppm	
Xylene (CAS 1330-20-7)	TLV	109 mg/m <sup>3</sup> 25 ppm	

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value	
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm	
Butane (CAS 106-97-8)	TWA	1500 mg/m <sup>3</sup> 800 ppm	
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m <sup>3</sup>	
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup> 1000 ppm	
Xylene (CAS 1330-20-7)	STEL	450 mg/m <sup>3</sup> 100 ppm	
	TWA	200 mg/m <sup>3</sup> 50 ppm	

**Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	1500 mg/m <sup>3</sup> 630 ppm	
	TWA	1200 mg/m <sup>3</sup> 500 ppm	
Butane (CAS 106-97-8)	STEL	2400 mg/m <sup>3</sup> 1000 ppm	
	TWA	1900 mg/m <sup>3</sup> 800 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,5 mg/m <sup>3</sup>	
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	500 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	TWA	0,01 mg/m <sup>3</sup>	Respirable.
Propane (CAS 74-98-6)	STEL	2000 mg/m <sup>3</sup> 1100 ppm	
	TWA	1500 mg/m <sup>3</sup> 800 ppm	
Xylene (CAS 1330-20-7)	STEL	440 mg/m <sup>3</sup> 100 ppm	
	TWA	220 mg/m <sup>3</sup> 50 ppm	

**France. OELs. Indicative Occupational Exposure Limits as Prescribed by Order of 30 June 2004, as amended**

Components	Type	Value	Form
C.I. Pigment black 028 (CAS 68186-91-4)	VME	0,2 mg/m3	Inhalable fraction.
		0,05 mg/m3	Respirable fraction.
Chromium (CAS 7440-47-3)	VME	2 mg/m3	

**France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended**

Components	Type	Value	
Acetone (CAS 67-64-1)	VLE	2420 mg/m3	
		1000 ppm	
		1210 mg/m3	
Xylene (CAS 1330-20-7)	VLE	500 ppm	
		442 mg/m3	
		100 ppm	
	VME	221 mg/m3	
		50 ppm	

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value	
Acetone (CAS 67-64-1)	VLE	2420 mg/m3	
		<b>Regulatory status:</b> Regulatory binding (VRC)	1000 ppm
		<b>Regulatory status:</b> Regulatory binding (VRC)	VME
		<b>Regulatory status:</b> Regulatory binding (VRC)	1210 mg/m3
		<b>Regulatory status:</b> Regulatory binding (VRC)	500 ppm
		<b>Regulatory status:</b> Regulatory binding (VRC)	
Butane (CAS 106-97-8)	VME	1900 mg/m3	
		<b>Regulatory status:</b> Indicative limit (VL)	800 ppm
		<b>Regulatory status:</b> Indicative limit (VL)	
C.I. Pigment black 028 (CAS 68186-91-4)	VME	2 mg/m3	
		<b>Regulatory status:</b> Regulatory indicative (VRI)	
Nickel (CAS 7440-02-0)	VME	1 mg/m3	
		<b>Regulatory status:</b> Indicative limit (VL)	
Xylene (CAS 1330-20-7)	VLE	442 mg/m3	
		<b>Regulatory status:</b> Regulatory binding (VRC)	100 ppm
		<b>Regulatory status:</b> Regulatory binding (VRC)	VME
		<b>Regulatory status:</b> Regulatory binding (VRC)	221 mg/m3
		<b>Regulatory status:</b> Regulatory binding (VRC)	50 ppm
		<b>Regulatory status:</b> Regulatory binding (VRC)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	1200 mg/m3	
		500 ppm	
Butane (CAS 106-97-8)	TWA	2400 mg/m3	
		1000 ppm	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	5 mg/m3	Respirable aerosol fraction
		350 mg/m3	Vapour.

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Propane (CAS 74-98-6)	TWA	50 ppm	Vapour.
		1800 mg/m3 1000 ppm	
Xylene (CAS 1330-20-7)	TWA	220 mg/m3	
		50 ppm	

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	AGW	1200 mg/m3 500 ppm	
Butane (CAS 106-97-8)	AGW	2400 mg/m3 1000 ppm	
Butanone oxime (CAS 96-29-7)	AGW	1 mg/m3	
C.I. Pigment black 028 (CAS 68186-91-4)	AGW	0,3 ppm 2 mg/m3	Inhalable fraction.
Chromium (CAS 7440-47-3)	AGW	2 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	AGW	300 mg/m3	
Nickel (CAS 7440-02-0)	AGW	0,03 mg/m3	Inhalable fraction.
		0,006 mg/m3	Respirable fraction.
Propane (CAS 74-98-6)	AGW	1800 mg/m3 1000 ppm	
Xylene (CAS 1330-20-7)	AGW	200 mg/m3	

**Greece. OELs, Presidential Decree No. 307/1986, as amended**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	3560 mg/m3
	TWA	1780 mg/m3
Butane (CAS 106-97-8)	TWA	2350 mg/m3
		1000 ppm
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,5 mg/m3
Chromium (CAS 7440-47-3)	TWA	1 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Xylene (CAS 1330-20-7)	STEL	650 mg/m3
		150 ppm
	TWA	435 mg/m3 100 ppm

**Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
Butane (CAS 106-97-8)	STEL	9400 mg/m3
	TWA	2350 mg/m3
C.I. Pigment black 028 (CAS 68186-91-4)	STEL	2 mg/m3
	TWA	0,1 mg/m3
Chromium (CAS 7440-47-3)	TWA	2 mg/m3
Xylene (CAS 1330-20-7)	STEL	442 mg/m3

**Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>	
	TWA	221 mg/m <sup>3</sup>	
<b>Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended</b>			
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Acetone (CAS 67-64-1)	TWA	600 mg/m <sup>3</sup> 250 ppm	
Butane (CAS 106-97-8)	TWA	1200 mg/m <sup>3</sup> 500 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	STEL	5 mg/m <sup>3</sup>	Total dust.
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>	Dust.
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m <sup>3</sup>	Dust.
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup> 1000 ppm	
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup> 100 ppm	
	TWA	109 mg/m <sup>3</sup> 25 ppm	

**Ireland. OELVs, Schedules 1 & 2, Code of Practise for Chemical Agents and Carcinogens Regulations**

<b>Components</b>	<b>Type</b>	<b>Value</b>	
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Butanone oxime (CAS 96-29-7)	STEL	33 mg/m <sup>3</sup> 10 ppm	
	TWA	10 mg/m <sup>3</sup> 3 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>	
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m <sup>3</sup>	
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup> 100 ppm	
	TWA	221 mg/m <sup>3</sup> 50 ppm	

**Italy. OELs**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,5 mg/m <sup>3</sup>	
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>	
Nickel (CAS 7440-02-0)	TWA	1,5 mg/m <sup>3</sup>	Inhalable fraction.
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup> 100 ppm	
	TWA	221 mg/m <sup>3</sup> 50 ppm	

**Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Butane (CAS 106-97-8)	STEL	300 mg/m <sup>3</sup>
	TWA	300 mg/m <sup>3</sup>
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m <sup>3</sup>
Propane (CAS 74-98-6)	STEL	300 mg/m <sup>3</sup>
	TWA	100 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	2420 mg/m <sup>3</sup>
		1000 ppm
	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)	TWA	20 mg/m <sup>3</sup>
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	500 mg/m <sup>3</sup>
	TWA	350 mg/m <sup>3</sup>
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>

**Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Netherlands. OELs per Annex XIII of Working Conditions Regulation (Government Gazette no. 252, 29 December 2006), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	2420 mg/m <sup>3</sup>
	TWA	1210 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
	TWA	210 mg/m <sup>3</sup>

**Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TLV	295 mg/m <sup>3</sup>
		125 ppm
Butane (CAS 106-97-8)	TLV	600 mg/m <sup>3</sup>
		250 ppm
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TLV	275 mg/m <sup>3</sup>
		40 ppm
Nickel (CAS 7440-02-0)	TLV	0,05 mg/m <sup>3</sup>
Propane (CAS 74-98-6)	TLV	900 mg/m <sup>3</sup>
		500 ppm
Xylene (CAS 1330-20-7)	TLV	108 mg/m <sup>3</sup>
		25 ppm

**Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	1800 mg/m <sup>3</sup>
	TWA	600 mg/m <sup>3</sup>
Butane (CAS 106-97-8)	STEL	3000 mg/m <sup>3</sup>
	TWA	1900 mg/m <sup>3</sup>
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,5 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>
Nickel (CAS 7440-02-0)	TWA	0,25 mg/m <sup>3</sup>
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	200 mg/m <sup>3</sup>
	TWA	100 mg/m <sup>3</sup>

**Portugal. Decree-Law No. 24/2012, Occupational Exposure Limit Values, Annex II, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
	TWA	1000 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,1 mg/m3	Inhalable fraction.
		0,02 mg/m3	Respirable fraction.
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3	
Nickel (CAS 7440-02-0)	TWA	1,5 mg/m3	Inhalable fraction.
Propane (CAS 74-98-6)	TWA	2500 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	1210 mg/m3	
		500 ppm	
Butane (CAS 106-97-8)	STEL	1500 mg/m3	
	TWA	1200 mg/m3	
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Nickel (CAS 7440-02-0)	STEL	0,5 mg/m3	
	TWA	0,1 mg/m3	
Propane (CAS 74-98-6)	STEL	1800 mg/m3	
		1000 ppm	
	TWA	1400 mg/m3	
Xylene (CAS 1330-20-7)		778 ppm	
	STEL	442 mg/m3	
	TWA	100 ppm	
		221 mg/m3	
		50 ppm	

**Slovakia. OELs for carcinogens and mutagens. Regulation No. 356/2006 on carcinogenic and mutagenic substances, as amended**

Components	Type	Value	Form
Butane (CAS 106-97-8)	TWA	2400 mg/m3	
		1000 ppm	
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m3	Inhalable fraction.

**Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	1210 mg/m3	
		500 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,2 mg/m3	Inhalable fraction.
		0,05 mg/m3	Respirable fraction.
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Iron (Massive metal) (CAS 7439-89-6)	TWA	6 mg/m3	
Xylene (CAS 1330-20-7)	TWA	221 mg/m3	
		50 ppm	

**Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)**

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup> 100 ppm

**Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Ann. I 100/2001), as amended**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	KTV	2420 mg/m <sup>3</sup> 1000 ppm	
Butane (CAS 106-97-8)	KTV	9600 mg/m <sup>3</sup> 4000 ppm	
Butanone oxime (CAS 96-29-7)	KTV	8 mg/m <sup>3</sup> 2,4 ppm	
Chromium (CAS 7440-47-3)	KTV	2 mg/m <sup>3</sup>	Inhalable fraction.
Nickel (CAS 7440-02-0)	KTV	0,048 mg/m <sup>3</sup>	Respirable fraction.
Propane (CAS 74-98-6)	KTV	7200 mg/m <sup>3</sup> 4000 ppm	
Xylene (CAS 1330-20-7)	KTV	442 mg/m <sup>3</sup> 100 ppm	

**Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm	
Butane (CAS 106-97-8)	TWA	2400 mg/m <sup>3</sup> 1000 ppm	
Butanone oxime (CAS 96-29-7)	TWA	1 mg/m <sup>3</sup> 0,3 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>	Inhalable fraction.
		0,2 mg/m <sup>3</sup>	Inhalable fraction.
		0,05 mg/m <sup>3</sup>	Respirable fraction.
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	0,006 mg/m <sup>3</sup>	Respirable fraction.
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup> 1000 ppm	
Xylene (CAS 1330-20-7)	TWA	221 mg/m <sup>3</sup> 50 ppm	

**Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>
Nickel (CAS 7440-02-0)	TWA	1 mg/m <sup>3</sup>
Propane (CAS 74-98-6)	TWA	1000 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup> 100 ppm
	TWA	221 mg/m <sup>3</sup>

**Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)**

Components	Type	Value
		50 ppm

**Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	1200 mg/m3	
		500 ppm	
	TWA	600 mg/m3	
Chromium (CAS 7440-47-3)	TWA	250 ppm	
	TWA	0,5 mg/m3	Total dust.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	500 mg/m3	
	TWA	350 mg/m3	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	Ceiling	442 mg/m3	
		100 ppm	
	TWA	221 mg/m3	
		50 ppm	

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	2400 mg/m3	
		1000 ppm	
	TWA	1200 mg/m3	
Butane (CAS 106-97-8)	STEL	500 ppm	
		7600 mg/m3	
	TWA	3200 ppm	
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	1900 mg/m3	
	TWA	0,5 mg/m3	Inhalable fraction.
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3	Inhalable fraction.
	STEL	700 mg/m3	Vapour.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)		100 ppm	Vapour.
	TWA	5 mg/m3	Aerosol
		350 mg/m3	Vapour.
Nickel (CAS 7440-02-0)		50 ppm	Vapour.
	TWA	0,5 mg/m3	Inhalable fraction.
Propane (CAS 74-98-6)	STEL	7200 mg/m3	
		4000 ppm	
	TWA	1800 mg/m3	
Xylene (CAS 1330-20-7)	STEL	1000 ppm	
		440 mg/m3	
	TWA	100 ppm	
		220 mg/m3	
		50 ppm	

**UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	3620 mg/m3

**UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1**

Components	Type	Value
		1500 ppm
	TWA	1210 mg/m <sup>3</sup>
		500 ppm
Butane (CAS 106-97-8)	STEL	1810 mg/m <sup>3</sup>
		750 ppm
	TWA	1450 mg/m <sup>3</sup>
		600 ppm
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	0,5 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m <sup>3</sup>
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	441 mg/m <sup>3</sup>
		100 ppm
	TWA	220 mg/m <sup>3</sup>
		50 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup>
		500 ppm
C.I. Pigment black 028 (CAS 68186-91-4)	TWA	2 mg/m <sup>3</sup>
Chromium (CAS 7440-47-3)	TWA	2 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	442 mg/m <sup>3</sup>
		100 ppm
	TWA	221 mg/m <sup>3</sup>
		50 ppm

**Biological limit values**

**Croatia. BELs (BGV). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and BELs, Annex IV (NN 91/2018), as amended**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	20 mg/g	Acetone	Creatinine in urine	*
	20 mg/l	Acetone	Blood	*
	0,34 mmol/l	Acetone	Blood	*
	39 mmol/mol	Acetone	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1,5 g/g	Methylhippuric acids	Creatinine in urine	*
	1,5 mg/l	xylene	Blood	*
	0,88 mol/mol	Methylhippuric acids	Creatinine in urine	*
	14,13 umol/l	xylene	Blood	*

\* - For sampling details, please see the source document.

**Czech Republic. BELs. Government Decree 432/2003 Sb., as amended**

Components	Value	Determinant	Specimen	Sampling Time
Chromium (CAS 7440-47-3)	0,065 µmol/mmol	Total chromium	Creatinine in urine	*
	0,03 mg/g	Total chromium	Creatinine in urine	*
Nickel (CAS 7440-02-0)	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*

**Czech Republic. BELs. Government Decree 432/2003 Sb., as amended**

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling Time
Nickel (CAS 7440-02-0)	0,1 µmol/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

\* - For sampling details, please see the source document.

**France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS), ND 2065)**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	100 mg/l	Acétone	Urine	*
Xylene (CAS 1330-20-7)	1500 mg/g	Acides méthylhippuriques	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	80 mg/l	ACETON	Urine	*
Xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-) säure (alle Isomere)	Urine	*

\* - For sampling details, please see the source document.

**Hungary. BELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 3&4, as amended**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	1380 µmol/l	Acetone	Urine	*
	80 mg/l	Acetone	Urine	*
C.I. Pigment black 028 (CAS 68186-91-4)	0,022 µmol/mmol	chromium	Creatinine in urine	*
	0,01 mg/g	chromium	Creatinine in urine	*
Chromium (CAS 7440-47-3)	0,022 µmol/mmol	chromium	Creatinine in urine	*
	0,01 mg/g	chromium	Creatinine in urine	*
Nickel (CAS 7440-02-0)	0,051 µmol/l	Nickel	Urine	*
	0,003 mg/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*
	1500 mg/g	methyl hippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	53,36 mg/g	Acetone	Creatinine in urine	*
	80 mg/l	Acetone	Urine	*
Xylene (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*
	1,5 mg/l	xylene	Blood	*

\* - For sampling details, please see the source document.

**Spain. BELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 3-Valores Límite Biológicos (VLB)**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetona	Urine	*
Xylene (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle BAT-Werte**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	80 mg/l	ACETON	Urine	*
Nickel (CAS 7440-02-0)	45 µg/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	2 g/l	Methylhippursäuren	Urine	*

\* - For sampling details, please see the source document.

**UK. BELs. Biological Monitoring Guidance Values (BMGVs) (EH40/2005 (Fourth Edition 2020)), Table 2**

Components	Value	Determinant	Specimen	Sampling Time
Chromium (CAS 7440-47-3)	10 µmol/mol	Chromium	Creatinine in urine	*
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines****Austria. MAK List**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Belgium OELs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Bulgaria OELs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Croatia ELVs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Czech Republic PELs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Denmark GV: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Estonia OELs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**EU Exposure Limit Values: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Finland Exposure Limit Values: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**France INRS: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**France Mandatory OELs (VLEP): Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Germany DFG MAK (advisory): Skin designation**

Butanone oxime (CAS 96-29-7) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Germany TRGS 900 Limit Values: Skin designation**

Butanone oxime (CAS 96-29-7) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Greece OEL: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Hungary OELs: Skin designation**

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

**Iceland OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Ireland Exposure Limit Values: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Italy OELs: Skin designation**

Xylene (CAS 1330-20-7)	Danger of cutaneous absorption
------------------------	--------------------------------

**Latvia OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Lithuania OELs: Skin designation**

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

**Luxembourg OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Malta OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Netherlands OELs (binding): Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Norway Exposure Limit Values: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Portugal OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Romania OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Slovakia OELs for Carcinogens and Mutagens: Skin designation**

Nickel (CAS 7440-02-0)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Slovakia OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Butanone oxime (CAS 96-29-7)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

**Spain OELs: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Sweden Threshold Limit Values: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Switzerland SUVA Limit Values at the Workplace: Skin designation**

Xylene (CAS 1330-20-7)	Can be absorbed through the skin.
------------------------	-----------------------------------

**UK EH40 WEL: Skin designation**

Nickel (CAS 7440-02-0)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

**8.2. Exposure controls****Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide easy access to water supply and eye wash facilities.

**Individual protection measures, such as personal protective equipment****General information**

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection**

Wear safety glasses with side shields (or goggles) and a face shield. Wear a full-face respirator, if needed. Eye protection should meet standard EN 166.

**Skin protection****- Hand protection**

Wear suitable gloves tested to EN374. Glove material: Nitrile. Use gloves with breakthrough time of 15 +/- 15 minutes. Minimum glove thickness 0.381 (15 mil) mm. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**- Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear respiratory protection with combination filter (dust and gas filter) during spraying operations. Use filter type (ABEK2/P3) according to EN 143. Check with respiratory protective equipment suppliers.

<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>Hygiene measures</b>	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol - Pressurized liquid (spray).
<b>Colour</b>	Grey.
<b>Odour</b>	Characteristic of solvents.
<b>Odour threshold</b>	Property has not been measured.
<b>Melting point/freezing point</b>	> -29 °C (> -20,2 °F)
<b>Boiling point or initial boiling point and boiling range</b>	> 56 °C (> 132,8 °F)
<b>Flammability</b>	Extremely flammable aerosol.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	0,6 %
<b>Explosive limit – upper (%)</b>	12,8 %
<b>Flash point</b>	Not applicable, product is an aerosol dispenser.
<b>Auto-ignition temperature</b>	> 236 °C (> 456,8 °F) (liquid)
<b>Decomposition temperature</b>	229,7 °C (445,5 °F) (liquid)
<b>pH</b>	Not applicable (material is insoluble in water).
<b>Kinematic viscosity</b>	2700 mm <sup>2</sup> /s (25 °C (77 °F))
<b>Solubility</b>	
<b>Solubility (water)</b>	(< 0,1%) Insoluble in water.
<b>Partition coefficient (n-octanol/water) (log value)</b>	Not applicable, product is a mixture.
<b>Vapour pressure</b>	70 psi (20 °C (68 °F))
<b>Density and/or relative density</b>	
<b>Density</b>	1,11 g/cm <sup>3</sup> (25 °C (77 °F))
<b>Relative density</b>	1,11 (Water=1) (25 °C (77 °F))
<b>Vapour density</b>	9,6 (Air=1) (25 °C (77 °F))
<b>Particle characteristics</b>	
<b>Particle size</b>	Does not contain nanomaterials.
<b>9.2. Other information</b>	
<b>9.2.1. Information with regard to physical hazard classes</b>	No relevant additional information available.
<b>9.2.2. Other safety characteristics</b>	
<b>Evaporation rate</b>	Property has not been measured.
<b>Viscosity</b>	Property has not been measured.
<b>VOC</b>	MIR CA < 1,25

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Contents under pressure. Do not puncture. Protect against direct sunlight. Avoid heat, sparks, open flames and other ignition sources. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Contact with incompatible materials.

**10.5. Incompatible materials**

Strong oxidising agents. Strong acids. Halogens. Chlorine.

**10.6. Hazardous decomposition products**

Thermal decomposition of this product can generate carbon monoxide and carbon dioxide. Fumes of metal oxides. Chlorine compounds. Fluorine compounds.

**SECTION 11: Toxicological information****General information**

Occupational exposure to the substance or mixture may cause adverse effects.

**Information on likely routes of exposure****Inhalation**

Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure by inhalation.

**Skin contact**

Causes skin irritation. May cause an allergic skin reaction. May be absorbed through the skin.

**Eye contact**

Causes serious eye irritation.

**Ingestion**

May cause discomfort if swallowed.

**Symptoms**

May cause drowsiness and dizziness. Narcosis. Headache. Fatigue. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Not expected to be acutely toxic.

**Components****Species****Test Results**

Acetone (CAS 67-64-1)

**Acute****Dermal**

LD50

Rabbit

&gt; 15700 mg/kg, 24 Hours

**Inhalation***Vapour*

LC50

Rat

76 mg/l, 4 Hours

**Oral**

LD50

Rat

5800 mg/kg

Butane (CAS 106-97-8)

**Acute****Inhalation**

LC50

Rat

658 mg/l, 4 Hours

Butanone oxime (CAS 96-29-7)

**Acute****Dermal**

LD50

Rabbit

&gt; 1000 mg/kg, 24 Hours

**Oral**

LD50

Rat

&gt; 900 mg/kg

Propane (CAS 74-98-6)

**Acute****Inhalation***Gas*

LC50

Rat

&gt; 80000 ppm, 15 Minutes

Xylene (CAS 1330-20-7)

**Acute****Oral**

LD50

Rat

3523 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory sensitisation**

Based on available data, the classification criteria are not met.

**Skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** May cause cancer.

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

Butanone oxime (CAS 96-29-7)

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)	2B Possibly carcinogenic to humans.
C.I. Pigment black 028 (CAS 68186-91-4)	3 Not classifiable as to carcinogenicity to humans.
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Butanone oxime (CAS 96-29-7) Carcinogenic, Category 2.

Nickel (CAS 7440-02-0) Carcinogenic, Category 2.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child by inhalation.

**Specific target organ toxicity - single exposure** May cause drowsiness and dizziness.

**Specific target organ toxicity - repeated exposure** May cause damage to organs (respiratory tract) through prolonged or repeated exposure by inhalation.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Mixture versus substance information** No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

**Other information** Symptoms may be delayed.

**SECTION 12: Ecological information**

**12.1. Toxicity** Toxic to aquatic life with long lasting effects.

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	LC50	Daphnia pulex	8800 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	7163 mg/l, 96 Hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	> 79 mg/l, 21 days
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2,9 mg/l, 96 hours
Nickel (CAS 7440-02-0)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1 mg/l, 48 hours
	LC50	Calanoid copepod (Eurytemora affinis)	>= 7,35 - <= 12,12 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2,6 mg/l, 96 hours

**12.2. Persistence and degradability** No data is available on the degradability of this product.

**12.3. Bioaccumulative potential**

**Partition coefficient n-octanol/water (log Kow)** Not applicable, product is a mixture.

Acetone (CAS 67-64-1)	-0,24
Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)	3,6
Butane (CAS 106-97-8)	2,89

<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	The product is insoluble in water. Not expected to be mobile in soil.
<b>12.5. Results of PBT and vPvB assessment</b>	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
<b>12.6. Endocrine disrupting properties</b>	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
<b>12.7. Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.

#### 12.8. Additional information

##### Estonia Dangerous substances in soil Data

Chromium (CAS 7440-47-3)	Chromium (Cr) 100 mg/kg Chromium (Cr) 300 mg/kg Chromium (Cr) 800 mg/kg
Nickel (CAS 7440-02-0)	Nickel (Ni) 150 mg/kg Nickel (Ni) 50 mg/kg Nickel (Ni) 500 mg/kg

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. 08 01 11*
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Hazard No. (ADR)</b>	-
<b>Tunnel restriction code</b>	D
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	Yes
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### RID

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	Yes

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### ADN

**14.1. UN number** UN1950  
**14.2. UN proper shipping name** AEROSOLS, flammable  
**14.3. Transport hazard class(es)**  
    **Class** 2.1  
    **Subsidiary risk** -  
    **Label(s)** 2.1  
**14.4. Packing group** -  
**14.5. Environmental hazards** Yes  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IATA

**14.1. UN number** UN1950  
**14.2. UN proper shipping name** Aerosols, flammable  
**14.3. Transport hazard class(es)**  
    **Class** 2.1  
    **Subsidiary risk** -  
    **Label(s)** 2.1  
**14.4. Packing group** -  
**14.5. Environmental hazards** Yes  
**ERG Code** 10L  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

**14.1. UN number** UN1950  
**14.2. UN proper shipping name** AEROSOLS, flammable  
**14.3. Transport hazard class(es)**  
    **Class** 2  
    **Subsidiary risk** -  
**14.4. Packing group** -  
**14.5. Environmental hazards**  
    **Marine pollutant** Yes  
**EmS** F-D, S-U  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**14.7. Maritime transport in bulk according to IMO instruments** Not established.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Acetone (CAS 67-64-1)

Chromium (CAS 7440-47-3)

Nickel (CAS 7440-02-0)

Xylene (CAS 1330-20-7)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered**

Acetone (CAS 67-64-1)	40
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	3
Xylene (CAS 1330-20-7)	75
Butanone oxime (CAS 96-29-7)	

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Butanone oxime (CAS 96-29-7)

**Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended**

Not listed.

**Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended**

Acetone (CAS 67-64-1) ACETONE

**Other EU regulations**

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances  
Hazard categories in accordance with Regulation (EC) No 1272/2008  
- P3a FLAMMABLE AEROSOLS  
- P3a FLAMMABLE AEROSOLS  
- P3b FLAMMABLE AEROSOLS  
- P3b FLAMMABLE AEROSOLS  
- P3b FLAMMABLE AEROSOLS  
- E2 Hazardous to the Aquatic Environment Chronic

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC, as amended.

**Contains a substance which is included on the TRGS 907 list of registry of sensitizing substances**

Nickel (CAS 7440-02-0) Nickelverbindungen, Wasserlösliche insbesondere Ni-sulfat und Ni-dichlorid

**France regulations**

**France INRS Table of Occupational Diseases**

Acetone (CAS 67-64-1)	Affections engendrées par les solvants organiques liquides à usage professionnel : hydrocarbures liquides aliphatiques ou cycliques saturés ou insaturés et leurs mélanges; hydrocarbures halogénés liquides; dérivés nitrés des hydrocarbures aliphatiques; al 84
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Affections engendrées par les solvants organiques liquides à usage professionnel : hydrocarbures liquides aliphatiques ou cycliques saturés ou insaturés et leurs mélanges; hydrocarbures halogénés liquides; dérivés nitrés des hydrocarbures aliphatiques; al 84

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).  
ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.  
EC50: Effective Concentration 50%.  
IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.  
IMO: International Maritime Organization.  
LC50: Lethal Concentration 50%.  
LD50: Lethal Dose 50%.  
PBT: Persistent, bioaccumulative, toxic.  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
TWA : Time Weighed Average Value.  
vPvB: very Persistent, very Bioaccumulative.

#### References

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices  
ECHA: European Chemical Agency.  
EPA: AQUIRE database  
HSDB® - Hazardous Substances Data Bank  
IARC Monographs. Overall Evaluation of Carcinogenicity  
National Toxicology Program (NTP) Report on Carcinogens  
NLM: Hazardous Substances Data Base

#### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

#### Full text of any statements, which are not written out in full under sections 2 to 15

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H370 Causes damage to organs.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

#### Training information

Follow training instructions when handling this material.

#### Disclaimer

Stainless Steel Coatings, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.